

# LPS<sup>®</sup> CFC FREE



## FEATURES

- Ideal for electrical/electronic and fine parts
- Cleans and degreases delicate precision mechanisms
- Penetrating action removes oil, grease, dirt, flux and other contaminants
- Does not contain chlorinated solvents
- Fast evaporation
- No residue & safe on plastics
- Meets or exceeds: McDonnell Douglas CSD #1; AMS 1525B; ASTM F-519, Type 1c; MIL-PRF-29608 Section 3.6 Type C
- Inverta Spray Valve lets you spray in an upright or inverted position

## PACKAGES

### Net Contents

11 wt. oz. / 312 g/ 459 mL aerosol
1 gal. (3.78 liters)
5 gal. (18.93 liters)
55 gal. (208 liters)

### Part No.

03116
03101
03105
03155

## APPLICATIONS

- Cables
- Circuit Breakers
- Electric Motors
- Electronic Connectors
- Generators
- Hinges
- Ignition Systems
- Locks
- Micrometers
- Precision Open Gears
- Power Tools
- Relays
- Sliding Mechanisms
- Switch Gears



Nonfood Compounds Program Listed  
Category Code: K2 Registration # 059813  
(Aerosol); # 059814 (Bulk)



## PROPERTIES

### Flash Point:

<0°F (<-18°C)

### % Non-Volatiles:

50 ppm maximum

### % HCFCs:

0%

### KB Value:

31

### Specific Gravity:

0.665

### Surface Tension:

17.3 dynes/cm @

77°F (25°C)

### Propellant:

Carbon Dioxide

### VOC:

100%, 665 g/L,

5.55 lbs./gal.(bulk)

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : [WWW.LPSLABS.COM](http://WWW.LPSLABS.COM)

**LPS Laboratories** • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

**Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)**

©2012 LPS Laboratories • LPS<sup>®</sup> is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2068 • Rev. 5/2012